


K DO



→ 简介

NPFSR-K5 D NPFSR-  
K52D NPFSR-K52D.SH  
DO 250V AC  
IEC 6 508 SIL3 SC3  
SIS ESD

- 
- Proof Test
- Fail-safe
- 
- 
- 

→ 技术参数

电源参数

8 V ~ 32 V DC 24 V DC  
≤ . W / 24 V DC/

输入参数

≤ 45 mA/24 V DC  
≤ 4 ms  
≥ 00 ms  
≤ 5 Ω

DO

输出参数

NO (NPFSR-K5 D)  
2NO (NPFSR-K52D, NPFSR-K52D.SH)  
AgSnO<sub>2</sub>+Au plating  
5 A/250 V AC, 5 A/24 V DC  
(NPFSR-K5 D)  
( 3, 4) ≤ 5 A  
( 3, F ) 5 A  
( 3, F2) 2.5 A  
(NPFSR-K52D, NPFSR-K52D.SH)  
( 3, 4) 5 A  
(23, 24) 5 A  
80%

时间参数

≤ 50 ms  
≤ 50 ms

→ 适用型号

60

→ 功能框图

→ 外形结构

× × : 2.8mm× 0mm× 7mm  
(NPFSR-K5 D, NPFSR-K52D.SH)

